



Operating instructions

We congratulate you on your purchase and thank you for your trust in our products. Your new Sub-5 Clamp withstands highest stress and has been made to the latest and most efficient methods of design and manufacture. **This includes special features that must be considered for installation.**

For installation, make absolutely sure that both carbon loops make a perfect fit on the aluminum inlays.

The top edge of the carbon loops should be flush with the top edge of the inlays. Tighten the clamping screws maximum to **6 Nm**.

Sub-5 Clamp



Diameter:



Remember that the height of your new Sub-5 clamp is 15mm. Do not install your new clamp if a higher or narrower clamp is required for your frame. If the clamp does not fit, we offer our design clamp of 12 mm or 20 mm height.

Warranty:

We grant a warranty of two years from the date of purchase of our products. Warranty claims can only be accepted if a (copy of the) dealer invoice is available.

The warranty covers defects of material and workmanship; it does not cover defects due to:

- Normal wear and tear
- Improper use
- Non-compliance with the instructions for use.

Warranty claims must be settled on site and are at the discretion of the firm Mcfk. The warranty granted by the firm Mcfk does not include compensation of damage; particularly any indirect damage in connection with an accident, any other indirect or consequential damage are excluded from our warranty.

The satisfaction of our customers is important to us. For this reason, we usually treat problems with our products very generously, also outside the warranty period. Please clean and return the parts and add a brief written account (including your contact data) and a copy of the invoice of the consignment.